



- Notes
- 1) Unless otherwise indicated, connections 3" and smaller are NPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
 - 2) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
 - 3) For weight loadings and support requirements, refer to the suggested steel support drawing.
 - 4) The area above the fan discharge must be unobstructed.
 - 5) Piping must not be supported by the tower inlet or outlet connections.
 - 6) Unit weights include selected accessories.
 - 7) M = Motor location.

Right Hand Unit

Model Number	Shipping Weight	Operating Weight	Heaviest Section	"H"	"B"	"D"	"L"
PT2-0412A-1x1	3060	5490	2290	10'-1"	6'-4 3/8"	6'-8 1/4"	3'-2 3/8"
PT2-0412A-2x1	3400	5830	2630	11'-1"	7'-4 3/8"	7'-8 1/4"	3'-2 3/8"
PT2-0412A-3x1	3560	6110	2630	12'-0"	8'-3 3/8"	7'-8 1/4"	4'-1 3/8"
PT2-0412A-4x1	3800	6350	2870	13'-0"	9'-3 3/8"	8'-8 1/4"	4'-1 3/8"

ORDER NO:

DATE:



BALTIMORE AIRCOIL COMPANY

**PT2 Single Cell Unit Print
Direct Drive**

DRAWING NUMBER:
GEN-PT2-0412A