

Notes

1) Unless otherwise indicated, connections 3" and smaller are NPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.

2) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.

3) For weight loadings and support requirements, refer to the suggested steel support drawing.

4) The area above the fan discharge must be unobstructed.

5) Piping must not be supported by the tower inlet or outlet connections.

6) Unit weights include selected accessories.

7) M = Motor location.

Model Number	Shipping Weight	Operating Weight	Heaviest Section	"H"	"B"	"D"	"L"
PT2-1009A-1x4	18410	32190	3320	16'-0 1/4"	10'-2 1/4"	8'-4"	7'-1 3/8"
PT2-1009A-2x4	20020	33800	3670	17'-0 1/4"	11'-2 1/4"	9'-4"	7'-1 3/8"
PT2-1009A-3x4	21880	35660	3990	18'-0 1/4"	12'-2 1/4"	10'-4"	7'-1 3/8"
PT2-1009A-4x4	22860	39230	3990	20'-0 1/4"	14'-2 1/4"	10'-4"	9'-1 3/8"
PT2-1009A-5x4	23980	40360	4270	21'-0 1/4"	15'-2 1/4"	11'-4"	9'-1 3/8"

ORDER NO:

DATE:



PT2 Quad Cell Unit Print

Internal Belt Drive

DRAWING NUMBER: **GEN-PT2-1009A QUAD-CELL** Data Version 1.03 DWG Version 1.01

1/2 Ŷ

---- 4'-5 7/8" --