



Notes

- 1) Drawings are not to scale. Refer to submittal drawings for actual dimensions and weights. All dimensions are in feet and inches, Weights are in pounds.
- 2) Unless otherwise indicated, connections 3" and smaller are MPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 3) Dimensions showing location of coil and basin connections are approximate and should not be used for prefabrication of connecting piping.
- 4) For weight loadings and support requirements, refer to the suggested steel support drawing.
- 5) Heaviest section is the combined weight of fan and coil sections, refer to the rigging and assembly manual for suggested lifting method.
- 6) The area above the discharge must be unobstructed.
- 7) Do not support piping from unit connections. All necessary piping supports to be supplied by others.
- 8) M = Motor location.

| Model Number | Approx. Shipping Weight | Approx. Operating Weight | Heaviest Section Weight | F | H |
|--------------------|-------------------------|--------------------------|-------------------------|------------|-------------|
| PFI-1236N-2DXDS-X2 | 41180 | 62510 | 16410 | 4'-0 5/8" | 18'-0" |
| PFI-1236N-2DXES-X2 | 42880 | 64300 | 17260 | 4'-8 1/8" | 18'-7 1/2" |
| PFI-1236N-3DXDS-X2 | 47390 | 71430 | 19510 | 4'-0 5/8" | 18'-0" |
| PFI-1236N-3DXES-X2 | 50140 | 74280 | 20890 | 5'-3 5/8" | 19'-3" |
| PFI-1236N-4DXDS-X2 | 54140 | 80890 | 22890 | 4'-8 1/8" | 18'-7 1/2" |
| PFI-1236N-4DXES-X2 | 57010 | 83850 | 24320 | 5'-11 1/8" | 19'-10 1/2" |
| PFI-1236N-5DXES-X2 | 57520 | 84710 | 24570 | 6'-5 5/8" | 20'-5" |
| PFI-1236N-6DXES-X2 | 66730 | 97460 | 29180 | 7'-1 1/8" | 21'-0 1/2" |

ORDER NO:

DATE:



BALTIMORE AIRCOIL COMPANY

FACE C

**PFI Closed Circuit Cooling Tower
Tabulated Unit Print**

DRAWING NUMBER:
UP-PFI-1236