

## Notes

- 1) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
- 2) Unless otherwise indicated, connections 3" and smaller are MPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 3) Field piping should be fabricated at time of installation. Pre-fabrication of pipe work is not recommended.
- 4) Do not support piping from unit connections. All necessary piping supports to be supplied by others.
- 5) For weight loadings and support requirements, refer to the suggested unit support drawing.
- 6) The area above the fan discharge must be unobstructed.
- 7) Due to height limitations on truck shipments, some items shown may ship loose for field installation.
- 8) Weights and dimensions are for base structure units with no accessories or optional features, values may vary depending upon unit configuration.
- 9) Connection sizes and locations are selected for pump suction applications at the designed flow rates. Sizes and locations may vary depending upon configuration options and design conditions.
- 10) Inlet is Studded Bolt Circle for mating to a 150# class ASME Flange.




	Operating	Shipping	Heaviest Section
Model Number	Weight	Weight	Weight
XES15E-1212-07EN	13940	6090	6090
XES15E-1212-07FN	13980	6130	6130
XES15E-1212-07GC	14040	6190	6190
XES15E-1212-07GN	14040	6190	6190
XES15E-1212-07HC	14060	6210	6210
XES15E-1212-07HN	14060	6210	6210
S15E-1212-07JN	14160	6310	6310
S15E-1212-07KN	14190	6340	6340
S15E-1212-07LC	14440	6590	6590





Face C



ORDER NO:

DATE: 3/18/2014



Series 1500 Single Cell Unit Print 1212-07

DRAWING NUMBER:

UP-XE-S15E-1212-07