


## Notes


- 1) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.
- 2) Unless otherwise indicated, connections 3" and smaller are MPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.
- 3) Field piping should be fabricated at time of installation. Pre-fabrication of pipe work is not recommended.
- 4) Do not support piping from unit connections. All necessary piping supports to be supplied by others.
- 5) For weight loadings and support requirements, refer to the suggested unit support drawing.
- 6) The area above the fan discharge must be unobstructed.
- 7) Due to height limitations on truck shipments, some items shown may ship loose for field installation.
- 8) Weights and dimensions are for base structure units with no accessories or optional features, values may vary depending upon unit configuration.
- 9) Connection sizes and locations are selected for pump suction applications at the designed flow rates. Sizes and locations may vary depending upon configuration options and design conditions.
- 10) Inlet is Studded Bolt Circle for mating to a 150# class ASME Flange.



Model Number	Operating Weight	Shipping Weight	Heaviest Section Weight
XES15E-1218-07EN	23140	9350	9350
XES15E-1218-07FN	23200	9410	9410
XES15E-1218-07GN	23290	9500	9500
XES15E-1218-07HN	23320	9530	9530
S15E-1218-07JN	23470	9680	9680
S15E-1218-07KN	23510	9720	9720
S15E-1218-07LC	23890	10100	10100







Face C

Face A

ORDER NO:

DATE: 3/18/2014



Series 1500 Single Cell Unit Print 1218-07

DRAWING NUMBER:

**UP-XE-S15E-1218-07**