2014© Baltimore Aircoil Company. All Rights Reserved.

Notes

Face D

1) All dimensions are in feet and inches. Weights are in pounds and include options and accessories.

2) Unless otherwise indicated, connections 3" and smaller are MPT. Connections 4" and larger are grooved to suit a mechanical coupling and beveled for welding.

 Field piping should be fabricated at time of installation. Pre-fabrication of pipe work is not recommended.


 Do not support piping from unit connections. All necessary piping supports to be supplied by others.

5) For weight loadings and support requirements, refer to the suggested unit support drawing.6) The area above the fan discharge must be unobstructed.


7) Due to height limitations on truck shipments, some items shown may ship loose for field installation.

 Weights and dimensions are for base structure units with no accessories or optional features, values may vary depending upon unit configuration.

 9) Connection sizes and locations are selected for pump suction applications at the designed flow rates. Sizes and locations may vary depending upon configuration options and design conditions.
10) Inlet is Studded Bolt Circle for mating to a 150# class ASME Flange.




Model Number	Operating Weight	Shipping Weight	Heaviest Section Weight
XES15E-1285-06EN	8990	4200	4200
XES15E-1285-06FN	9010	4220	4220
XES15E-1285-06GN	9040	4250	4250
XES15E-1285-06HN	9050	4260	4260
S15E-1285-06JN	9100	4310	4310
S15E-1285-06KN	9110	4320	4320
S15E-1285-06LN	9240	4450	4450



Face B





Face A



Face C